


未注线性尺寸公差 Liner dimension tolerances						
0~6	6~10	>10~30	>30~60	>60~100	>100~160	>160
±0.2	±0.3	±0.5	±0.7	±1.0	±1.3	±1.6

REV	DESCRIPTION	DRW.	DATE
A	RELEASE		

UL 技术参数				
UL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	50	/
额定电流	Rated Current [A]	10	10	/
耐电压	Withstanding Voltage [V]	AC 1300V/1Min		
IEC 技术参数				
IEC Technical Data				
过压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	80	125	200
额定电流	Rated Current [A]	10	10	10
冲击电压	Rate Impulse Voltage [kV]	2.5	2.5	2.5
一般参数 Other Data				
线径范围	Wire Range [AWG/mm²]	/		
剥线长度	Stripping length [mm]	/		
位数范围	Poles	02~24P		
工作温度	Operating temperature [°C]	-40 ~ +105		
螺丝扭矩	Screw torque(Max) [mm]	/		
环保要求	RoHS Compliant	YES		

3	Pin_Header	Copper Alloy	SN Plated
2	Pin_Header	Copper Alloy	SN Plated
1	Housing	PA66GF	UL94-V0
ITEM	NAME	MATERIAL	NOTES



TYPE CUSTOMER DRAWING 客户图档		PROJECTION		TITLE PL1.5S-XX-3.50-07
DRFT	刘秀海	DATE	2026.03.15	
CHKD	曾裕辉	DATE	2026.03.15	DWG NO.
APPD	陈柏林	DATE	2026.03.15	

