








未注线性尺寸公差 Liner dimension tolerances						
0~6	6~10	>10~30	>30~60	>60~100	>100~160	>160
±0.2	±0.3	±0.5	±0.7	±1.0	±1.3	±1.6

REV	DESCRIPTION	DRW.	DATE
A	RELEASE		

UL 技术参数				
UL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	/	300
额定电流	Rated Current [A]	5	/	5
耐电压	Withstanding Voltage [V]	AC 1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	320	400
额定电流	Rated Current [A]	6	6	6
冲击电压	Rate Impulse Voltage [KV]	4	4	4
一般参数 Other Data				
线径范围	Wire Range [AWG/mm²]	20~16/0.5~1.5		
剥线长度	Stripping length [mm]	6~7		
位数范围	Poles	02~24P		
工作温度	Operating temperature [°C]	-40 ~ +105		
螺丝扭矩	Screw / torque(Max) [lbf.in]	/		
环保要求	RoHS Compliant	YES		



PCB LAYOUT

6	Spring	Stainless Steel	/
5	Pin_Header_1	Brass	SN Plated
4	Button	POM	Orange
3	Side_Cover	PA66%	UL94-V0
2	Side_Housing	PA66%	UL94-V0
1	Housing	PA66%	UL94-V0
ITEM	NAME	MATERIAL	NOTES

TYPE CUSTOMER DRAWING 客户图档		PROJECTION			 FORANY ELECTRIC
DRFT	刘秀海	DATE	2026. 06. 25	UNITS: MM	
CHKD	曾裕辉	DATE	2026. 06. 25	SCALE: 1:1	
APPD	陈柏林	DATE	2026. 06. 25	SHEET 1 OF 1	TITLE SP1-XX-5.0-02
					DWG NO.