





未注线性尺寸公差 Liner dimension tolerances						
0~6	6~10	>10~30	>30~60	>60~100	>100~160	>160
±0.2	±0.3	±0.5	±0.7	±1.0	±1.3	±1.6

REV	DESCRIPTION	DRW.	DATE
A	RELEASE		

UL 技术参数				
UL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	/	300
额定电流	Rated Current [A]	10	/	10
耐 电 压	Withstanding Voltage [V]	AC 1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	320	500
额定电流	Rated Current [A]	13.5	13.5	13.5
冲击电压	Rate Impulse Voltage [KV]	4	4	4
一般参数 Other Data				
线径范围	Wire Range [AWG/mm²]	20~16/0.8~1.5		
剥线长度	Stripping length [mm]	8~9		
位数范围	Poles	02~24P		
工作温度	Operating temperature [°C]	-40 ~ +105		
螺丝扭矩	Screw / torque(Max) [lbf.in]	/		
环保要求	RoHS Compliant	YES		



6	Spring	Stainless Steel	/
5	Pin Header	Brass	SN Plated
4	Button	POM	Orange
3	Side_Cover	PA66	UL94-V0
2	Side_Housing	PA66	UL94-V0
1	Housing	PA66	UL94-V0
ITEM	NAME	MATERIAL	NOTES



TYPE CUSTOMER DRAWING 客户图档		PROJECTION				TITLE SP1.5-XX-5.0-01
DRFT	刘秀海	DATE	2026. 06. 25	UNITS: MM		
CHKD	曾裕辉	DATE	2026. 06. 25	SCALE: 1:1	DWG NO.	
APPD	陈柏林	DATE	2026. 06. 25	SHEET 1 OF 1		